

### Next-generation wearable scanner delivers maximum functionality in a minimal footprint

The tiny RS409 Ring Scanner from Symbol Technologies offers the ideal blend of form and function, allowing unparalleled freedom of movement in scanning, picking, and sorting applications. Part of the WT4000 Series Wearable System, this lightweight device delivers hands-free ergonomic comfort, the latest in scanning technology, and the rugged design to endure everyday use indoors and outdoors. The RS409 can scan near or far, can be worn directly on the finger or over a gloved hand, and is ideal for a wide range of applications — from workers picking product in a warehouse or processing deliveries in a postal facility, to hospitality workers scanning lift tickets on a ski slope.

### Superior scanning performance

When it comes to scanning, the lightweight RS409 offers performance and reliability you can count on. The device delivers accurate reading of even poorly printed and damaged bar codes on the first scan. Its highly advanced retro-collective optical design provides an extremely wide working range — from one inch to over four feet — with rapid reading regardless of lighting conditions or bar code symbology. And the scanner's low power consumption ensures more-than-ample battery power for a full shift.

### Rugged design for reliable every day use

The rugged design offers improved impact protection for reliable operation in the roughest environments. The scan engine is better isolated and protected from the routine impacts and shocks associated with everyday drops and bumps. Fragile silicon mirrors have been replaced with a frictionless Liquid Polymer scan element that won't wear out. The trigger is built to last, rated for over one million actuations. And the new housing offers improved abrasion resistance in the most vulnerable spots.

### State-of-the-art ergonomics for ease of use and maintenance

The ergonomic design makes data capture a breeze in any environment. The RS409 is designed to provide maximum user comfort, regardless of hand size or preferred hand position. The new swivel feature allows users to easily switch from right to left hand use in seconds, eliminating time previously spent removing and re-threading the strap. And the removable finger strap is completely isolated from the scanner — each operator can now be issued a personal finger strap for improved hygiene.



#### FEATURES

#### BENEFITS

Hands-free scanning	Ring scanner design frees operator's hands to move packages, products or materials, helping to improve efficiency and productivity
SE955 scan engine	Provides superior scanning performance; ability to read even damaged or poorly printed bar codes
Retro-collective optical design	Provides extremely wide working range for increased productivity
Bright scan line and aim mode	Provides intuitive ease-of-use across the entire working range
New housing design	Improved abrasion resistance in areas most likely to wear
Die cast zinc scan engine chassis, single board construction, scan engine isolation	Improves impact protection for scan engine to ensure maximum reliability
Supports Reduced Space Symbology (RSS)	Broadens the range of your scanning capabilities and increases investment protection
New swivel feature	Enables easy switching from right to left hand use
Separate finger strap assembly	Improves hygiene and personalization; easy to replace
Better trigger ergonomics	Accommodates wide range of hand sizes; adapts to different hand positions
Uses improved connectors to attach to WT4000 Series system host	Maximizes device flexibility and host uptime
Oversize LED light pipe	Enables users to quickly and easily confirm completion of a scan
RoHS compliant	Meets RoHS requirements

## Maximum value

Whether your workers need both hands to pick fragile or other goods or need the comfort of hands-free scanning for scan intensive applications, the RS409 provides the features and functionality to streamline processes, help improve worker productivity — and deliver a rapid return on investment. With built-in durability, you can count on maximum device uptime for a remarkably low total cost of ownership. And since even the most intelligent products require a maintenance plan and a support strategy, Symbol provides a full complement of service offerings to maximize uptime and maintain peak performance.

For more information on the RS409, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at: [www.symbol.com/rs409](http://www.symbol.com/rs409)

## RS409 Specification Highlights

### Physical and Environmental Characteristics

Dimensions:	1.9 in. H x 1.4 in. W x 1.9 in. D 4.8 cm H x 3.6 cm W x 4.8 cm D
Weight:	2.0 oz./56.7 gm
Current:	92 mA typical/121 mA max (one LED on)
Standby Current:	12 µA typical/60 µA max
Voltage:	3.1 VDC to 3.6 VDC
Vcc Noise Level:	100 mV peak to peak max.

### Performance Characteristics

Light Source:	650nm LASER 1.55mW
Scan Rate:	92 min., 104 typical, 116 max. scans/sec (bidirectional)
Nominal Working Distance:	
Density:	5 mil 7.5 mil 10 mil 13 mil 20 mil 40 mil 55 mil
Code Type:	39 39 39 UPC 39 30 39
Far (Guaranteed):	4.75 in. 8.75 in. 13.25 in. 17.25 in. 21.5 in. 22.25 in. 27 in.
Far (Typical):	8.75 in. 14.25 in. N/A 24.25 in. 35.75 in. N/A 50.5 in.

Yaw:	± 50° from normal
Roll:	± 35° from vertical
Pitch:	± 65° from normal

### User Environment

Operating Temperature:	-4° to 122° F/-20° to 50° C
Storage Temperature:	-25° to 160° F/-40° to 70° C
Humidity:	5% to 95% non-condensing
Ambient Light Immunity:	Indoor – 450 ft. candles (4,844 lux) Outdoor – 10,000 ft. candles (107,640 lux)
Drop Specification:	Multiple drops to concrete: 4 ft./1.2 m across the operating temperature range
Environmental Sealing:	IP54

### Regulatory

Electrical Safety:	Certified to UL60950-1, CSA C22.2 No. 60950-1, EN60950-1, IEC 60950-1
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC and R&TT Directives, Australian AS/NZS 4268
Laser Safety:	CDRH Class II, IEC 60825-1 Class 2

## About Symbol Technologies

Symbol Technologies, Inc., The Enterprise Mobility Company™, is a recognized worldwide leader in enterprise mobility, delivering products and solutions that capture, move and manage information in real time to and from the point of business activity. Symbol enterprise mobility solutions integrate advanced data capture technology, mobile computing platforms, wireless infrastructure, mobility software and world-class services programs. Symbol enterprise mobility products and solutions are proven to increase workforce productivity, reduce operating costs, drive operational efficiencies and realize competitive advantages for the world's leading retailers, transportation and logistics companies, manufacturers, wholesale and distribution centers, government agencies and healthcare facilities. More information is available at [www.symbol.com](http://www.symbol.com)



**Corporate Headquarters**  
**Symbol Technologies, Inc.**  
One Symbol Plaza  
Holtsville, NY 11742-1300  
TEL: +1.800.722.6234  
+1.631.738.2400  
FAX: +1.631.738.5990

**For Asia Pacific Area**  
**Symbol Technologies Asia, Inc.**  
(Singapore Branch)  
Asia Pacific Division  
230 Victoria Street #12-06/10  
Bugis Junction Office Tower  
Singapore 188024  
TEL: +65.6796.9600  
FAX: +65.6796.7199

**For Europe, Middle East and Africa**  
**Symbol Technologies**  
EMEA Division  
Symbol Place, Winnersh Triangle  
Berkshire, England RG41 5TP  
TEL: +44.118.9457000  
FAX: +44.118.9457500

**For North America, Latin America and Canada**  
**Symbol Technologies**  
The Americas  
One Symbol Plaza  
Holtsville, NY 11742-1300  
TEL: +1.800.722.6234  
+1.631.738.2400  
FAX: +1.631.738.5990

**Symbol Web Site**  
For a complete list of Symbol subsidiaries and business partners worldwide contact us at:  
[www.symbol.com](http://www.symbol.com)  
**E-mail**  
[info@symbol.com](mailto:info@symbol.com)



DS-RS409 09/06

Part No. DS-RS409 Printed in USA 09/06 © Copyright 2006 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply. Specifications are subject to change without notice. Symbol® is a registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.