

**ProLite B1780SD-B1**

**Perfect choice for office**

The 17" ProLite B1780SD designed for business usage is a LED-backlit monitor with Height Adjustability and Screen Rotation allowing you to set the perfect position of the screen ensuring ergonomic posture and optimal viewing comfort. The 5ms response time and high contrast make the B1780SD ideal for a wide range of business applications. sRGB and gamma correction functions permit even the finest nuances of colour to be set accurately. The ProLite B1780SD includes DVI and VGA connectivity and is available in black and white.

**DISPLAY CHARACTERISTICS**

Diagonal	17"; 43cm
Panel	TN LED
Display area h x w	270.3 x 337.9 mm; 10.6" x 13.3"
Response time	5 ms
Static contrast	1000 : 1 typical
Advanced contrast	5 000 000 : 1 ACR
Brightness	250 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.264 x 0.264 mm
Native resolution	1280 x 1024 ( 1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	5 : 4

**POWER MANAGEMENT**

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	14 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

**DIMENSIONS / WEIGHT**

Dimensions w x h x d	370 x 399.5 (529.5) x 230 mm
Weight	4.4 kg

**INTERFACES / CONNECTORS / CONTROLLERS**

Analog input connector	VGA
Digital input connector	DVI-D
HDCP	yes

**SPECIAL FEATURES**

<b>Apple - Mac</b>	All iiyama monitors are compatible with Apple-Macintosh computers.
<b>Controls</b>	Via OSD in 9 languages (EN, DE, FR, NL, PL, RU, JP, Chinese - traditional and simplified) and 5 front controls (Power, Select/ Input, Scroll up/ Audio, Scroll down/ i-Style Colour, Menu)
<b>User controls</b>	auto adjust, luminance (contrast, brightness, ACR, ECO), input select, audio (volume, mute), colour adjust, information, manual image adjust (H./V. position, clock, phase, sharpness), setup menu (language select, OSD position, OSD time out, OSD background, opening logo, LED), recall
<b>Speakers</b>	2 x 1 W (Stereo)
<b>Anti-theft-device</b>	Kensington-lock™ prepared
<b>Safety</b>	CE, TÜV-Bauart, VCCI-B, TCO, GOST-R
<b>Height adjustment</b>	130 mm
<b>Rotation (pivot function)</b>	90°
<b>Swivel Stand</b>	90°; 45° left; 45° right
<b>Tilt angle</b>	22° up; 3° down
<b>VESA mounting</b>	100 x 100 mm
<b>Colour</b>	White, Black

**ACCESSORIES**

<b>Driver</b>	Windows 95 / 98 / 2000 / ME / XP / Vista / 7 / 8
<b>Included accessories</b>	power cable, DVI-D cable, audio cable, stand, cable holder, quick start guide, safety guide